

U.S. Department of
Homeland Security

United States
Coast Guard



Commandant
United States Coast Guard

2703 Martin Luther King Jr. Ave. SE
Washington, DC 20593-7509
Staff Symbol: CG-OES
Phone: 202-372-1431
Fax: 202-372-8382
Email: John.A.Meehan@uscg.mil

5760
August 21, 2014

Hyde Marine
Attn: Mark Riggio
2000 McClaren Woods Drive
Pittsburgh, PA 15108

ALTERNATE MANAGEMENT SYSTEM ACCEPTANCE

The Coast Guard has completed its review of the Alternate Management System (AMS) application submitted by Hyde Marine, Inc. (Hyde), for the Hyde Guardian ballast water treatment system (BWTS). This letter grants AMS acceptance in accordance with the requirements of 33 CFR 151.2026 for the following Hyde Marine BWTS:

- Hyde GUARDIAN™, incorporating models HG-60, -100, -150, -200, -250, -300, -350, -400, -450, -500, -600, -700, -800, -900, -1000, -1250, -1350, -1400, -1500, -1600, -2000, -2500, -3000, -4000, -5000, and -6000 and all approved filters and filter housings, as type approved by Lloyd's Register under the authority of the Maritime and Coastguard Agency (MCA) of the United Kingdom and as detailed in the renewed type approval certificate MCA 0900032/M3, issued April 14, 2014 and expiring April 13, 2016. This AMS acceptance letter is a reissue of a previous U.S. Coast Guard AMS acceptance letter for the Hyde Guardian BWTS dated April 15, 2013 with this reissuance necessitated by the renewal of the MCA type approval certificate.

The Hyde Guardian BWTS is assigned the following AMS identification number:

AMS-2013-Hyde-Guardian-001

Coast Guard acceptance of the Hyde Guardian BWTS as an AMS does not accord or imply conformance to or compliance with any other Federal, state, or local water discharge effluent limitations that may apply to the vessel on which the AMS operates or the regulatory regimes and locations within which it operates. The owner and operator of the vessel must comply with all applicable laws, regulations, and treaties, including the Clean Water Act and associated provisions of the Vessel General Permit (VGP); the Federal Insecticide, Fungicide, and Rodenticide Act of 1972, as amended (FIFRA); other Coast Guard safety regulations and requirements; and other applicable laws and regulations.

In accordance with 33 CFR 151.2026 (a)(5), the AMS application required the submittal of a type approval application for the BWTS. The type approval information submitted with the

August 21, 2014

AMS application does not have any bearing on the type approval status of the BWTS, nor does Coast Guard acceptance of the Hyde Guardian BWTS as an AMS indicate that the BWTS meets requirements for Coast Guard type approval.

The following conditions apply for the operation of the Hyde Guardian AMS in U.S. waters:

1. The AMS manufacturer must comply with all the general conditions of certification stipulated in the TA certificate issued by Lloyd's Register on behalf of the MCA, as referenced above. Revocation of type approval by the approving authority will result in revocation of this AMS acceptance. Copies of all reports required under the stated conditions of use must be submitted to the Office of Environmental Standards (OES-3) at the following address or email:

COMMANDANT (CG-OES-3)
United States Coast Guard Stop 7509
2703 Martin Luther King Jr. Ave SE
Washington DC 20593-7509
Tel: 202-372-1402
e-mail: environmental_standards@uscg.mil

2. Because this ballast water treatment system has not been adequately tested in freshwater, its use as an AMS is limited to the treatment of marine and brackish water with a practical salinity unit (PSU) concentration greater than 1.
3. Installation and repairs of the AMS must be performed in accordance with the manufacturer's instructions and approved by the flag administration or its representative.
4. Operation and maintenance must be conducted in accordance with all specifications and limiting conditions stipulated on the TA certificate and with the manufacturer's instructions, including any limitations posed by the environment (for example, water quality, temperature, salinity, or other parameters) or vessel operations (for example, voyage duration, pumping rates, or other constraints). The following specific conditions apply:
 - a. **Flow rates:** The flow rate of ballast water through the system should not exceed the treatment rated capacity (TRC) for the installed system, as specified on the TA certificate.
 - b. **UV intensity:** The UV intensity sensor should always read at 70% or greater of the full calibrated irradiance level at the operating power level. If the UV intensity falls below 70% at low power, the system must automatically increase to high power. If the UV intensity falls below 70% at high power, an audible and visual alarm must sound.
 - c. **Differential pressure across the filter:** The pressure differential across the filter should not exceed 1 bar. The system is set to back flush automatically at 0.7 bar

August 21, 2014

pressure differential, and an alarm is sounded by the control system when excessive back flushing (three or more consecutive back flushes) or high differential pressure (>1.0 bar) occurs.

A historical record documenting that the system has been operated within these criteria, including a record of any alarm conditions, shall be made available for review onboard the vessel.

5. If installed on a U.S. flag vessel, it must be shown that the system and installation comply with or provide an equivalent level of safety to the requirements of 46 CFR Subchapter F (Marine Engineering) and Subchapter J (Electrical Engineering). All electrical equipment located within hazardous areas must be explosion proof or intrinsically safe as certified by an independent laboratory recognized by USCG per 46 CFR 111.105-7.
6. Use of the AMS is specified in the ship's ballast water management plan (BW plan), required by 33CFR 151.2050(g). The BW plan must identify the following: (1) the ballast water management practices to be used in the event the AMS cannot be used, and (2) the personnel responsible for the operation, maintenance, and repair of the BWTS. An up-to-date record of the operation, maintenance, and repair of the BWTS must be maintained onboard the ship.
7. Any change in design, materials, manufacturing, or intended operational conditions of this BWTS without prior notification to, and acceptance by, the U. S. Coast Guard will automatically invalidate this AMS acceptance. Prior to any such change, the manufacturer of an AMS must notify the Commanding Officer, U. S. Coast Guard Marine Safety Center (MSC), at the following address or e-mail:

Commanding Officer (MSC)
Attn: Marine Safety Center
U.S. Coast Guard Stop 7410
4200 Wilson Blvd, Suite 400
Arlington VA 20598-7410
e-mail: msc@uscg.mil

The notification must include the following: (1) a description of the change, the reason it is required, and its intended advantages; (2) an explanation of any effect of the change on installation, operation, maintenance, or repair requirements; and (3) an indication of whether or not the original configuration of the BWTS will be discontinued.

8. If the installed AMS does not operate properly when treating ballast water intended for discharge in U.S. waters, the person directing the movement of the vessel must ensure that the problem is reported to the nearest Coast Guard Captain of the Port (COTP) or District Commander as soon as practicable. The Coast Guard shall be notified of any treatment system or component failures, irreparable damage to components of the AMS, frequent process upsets or out-of-bounds operating conditions, or other situations or process-related conditions that may reduce treatment effectiveness. The vessel may

August 21, 2014

continue to the next U.S. port of call, subject to the directions of the COTP or District Commander, as provided by 33 CFR 160.

9. All transport and handling of chemicals required for proper operation of the AMS must be conducted in accordance with 46 CFR 147 (Hazardous Ships' Stores), 49 CFR 171-180 (Hazardous Materials Regulations), and 46 CFR 98.30 (portable tanks), as appropriate.
10. Use of the AMS must be reported in the ship's ballast water management reports submitted to the National Ballast Information Clearinghouse, as required by 33CFR 151.2060, as follows:
 - a. In Section 4, report the number of tanks treated by the AMS in the space labeled "Underwent Alternative Management";
 - b. In Section 4, write the AMS identification number (AMS-2013-Hyde-Guardian-001) in the space labeled "Please specify alternative method(s) used, if any," and;
 - c. In Section 5, in the middle section titled "BW MANAGEMENT PRACTICES" identify the management method as "ALT" under the heading "Method (ER/FT/ALT)" for each tank for which the AMS was used.

The Coast Guard may suspend, withdraw or terminate the acceptance of this BWTS as an AMS in accordance with 46 CFR 2.75-40, 2.75-50(a) and 2.75-50(b), respectively.

A copy of this letter shall be provided to each vessel with this installed AMS and shall be available for review when the vessel is operating in U.S. waters.

I thank you for your dedicated efforts to seek out AMS acceptance, and we look forward to working with you throughout the type approval process. If you have any questions concerning this letter, you may contact Mr. John Meehan of my staff at John.A.Meehan@uscg.mil.

Sincerely,



R. E. BAILEY

Captain, U.S. Coast Guard

Office of Operating and Environmental Standards

By direction